


SAFETY DATA SHEET
APEX Superlube Mid Dens SM
Lubricant


Section 1: Identification

Product Identifier		
Product Name	APEX Superlube Mid Dens SM®	
Relevant identified uses of the substance or mixture and uses advised against		
Recommended use	Hazard Communication & Compliance	
Details of the supplier of the safety data sheet		
Manufacturer		
	APEX Advanced Technologies, LLC 4857-A West 130 th Street Cleveland OH 44135 United States Telephone (General) 615-459-0064	
Emergency telephone number		
Manufacturer	APEX Advanced Technologies, LLC	(216) 898-1595
	CHEMTREC	(800) 424-9300

Section 2: Hazard Identification

United States (US)		
According to OSHA 29 CFR 1910.1200 HCS	APEX Superlube Mid Dens SM	
Classification of the substance or mixture		
OSHA HCS 2012	• H316: Causes mild skin irritation	
Label elements		
OSHA HCS 2012		
	WARNING	
		
Hazard statements	<ul style="list-style-type: none"> • H316: Causes mild skin irritation • H320: May cause eye irritation. • H335: May cause respiratory irritation. 	
Precautionary statements		
	<ul style="list-style-type: none"> • P402+404: Store in a dry place. Store in a closed container • P403: Store in a well ventilated place. 	

SAFETY DATA SHEET
APEX Superlube Mid Dens SM
Lubricant

	<ul style="list-style-type: none"> P210: Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.
	<ul style="list-style-type: none"> P235: Keep cool.
Prevention	
	<ul style="list-style-type: none"> P261: Avoid breathing dust. [As modified by IV ATP]
	<ul style="list-style-type: none"> P264: Wash hands thoroughly after handling
Response	
	<ul style="list-style-type: none"> P370+P378: In case of fire: Use appropriate media for extinction.
	<ul style="list-style-type: none"> P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	<ul style="list-style-type: none"> P312: Call a POISON CENTER or doctor/physician if you feel unwell.
	<ul style="list-style-type: none"> P353: Rinse skin with water/shower.
	<ul style="list-style-type: none"> P332+P313: If skin irritation occurs: Get medical advice/attention.
Storage/Disposal	
	<ul style="list-style-type: none"> P402+404: Store in a dry place. Store in a closed container
	<ul style="list-style-type: none"> P403: Store in a well ventilated place.
	<ul style="list-style-type: none"> P210: Keep away from heat, sparks, open flames and/or hot surfaces. - No smoking.
	<ul style="list-style-type: none"> P235: Keep cool.
Other information	
NFPA	

Section 3 - Composition/Information on Ingredients

Substances		
	Material does not meet the criteria of a substance.	
Mixtures		
Component	CAS #	% by Wt.
Stearic Wax (mixture)	110-30-5	70% (max.)
Olefin Wax	9002-88-4	20% (max.)
Solid Saturated Hydrocarbon	68153-22-0	15% (max.)
Hydrated Amorphous Silica	112926-00-8	2% (max)
Proprietary surface agent	31570-04-4	1% (max.)

SAFETY DATA SHEET
APEX Superlube Mid Dens SM
Lubricant

Proprietary surface agent	149-57-5	1% (max)
---------------------------	----------	----------

Section 4: First-Aid Measures

Description of first aid measures	Call for emergency medical care. Keep victim warm and quiet. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.
Inhalation	Move patient to fresh air. Seek medical attention if respiratory irritation develops or if breathing becomes difficult.
Skin	Remove and isolate contaminated clothing and shoes. In case of contact with substance, immediately flush skin with running water for at least 20 minutes. For minor skin contact, avoid spreading material on unaffected skin. Wash exposed area thoroughly with soap and water. Seek medical attention if irritation develops.
Eye	Exposed eyes should be irrigated with water for at least 20 minutes. Seek medical attention if irritation develops.
Ingestion	If swallowed, give 3-4 glasses of water but do not induce vomiting. If vomiting does occur, give fluids again. Get medical attention to determine whether vomiting or evacuation of the stomach is necessary. Do not give anything by mouth to an unconscious or convulsing person. Most important symptoms and effects, both acute and delayed
	Refer to Section 11 - Toxicological Information.
Notes to Physician	All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred.

Section 5: Fire-Fighting Measures

Extinguishing Media		
Suitable Extinguishing Media	Flammable Properties:	Not available
	Flammable Limits:	Not available
	Auto-ignition Temperature:	Not available
	Hazardous Combustion Products:	Not available
Extinguishing Media and Fire Fighting Instructions	Small fires:	Water, carbon monoxide, dry chemical powder, dry sand, or foam.
	Large Fires:	Water spray, fog or alcohol-resistant foam. Move containers from fire area if you can do it without risk. Do not use straight streams. Dike fire control water for later disposal; do not scatter material.

SAFETY DATA SHEET
APEX Superlube Mid Dens SM
Lubricant

		Wear positive pressure, self-contained breathing apparatus (SCBA). Wear chemical protective clothing that is specifically recommended by the manufacturer. Structural firefighters' protective clothing is recommended for fire situations ONLY; it is not effective in spill situations.
--	--	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Section 6 - Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	
Personal Precautions	Wear appropriate protective equipment including respiratory protection as conditions warrant.
Methods and material for containment and cleaning up	
Containment/Clean-up Measures	If material is released or spilled, use vacuum for clean-up.

Section 7 - Handling and Storage

Precautions for safe handling	
Handling	Do not breathe dust. Avoid contact with eyes, skin and clothing.
Conditions for safe storage, including any incompatibilities	
Storage	Keep container closed. Keep away from incompatible materials. Store in a cool, dry area away from ignition sources and oxidizers.
Incompatible Materials or Ignition Sources	
	Store in a cool, dry area away from ignition sources and oxidizers.

Section 8 - Exposure Controls/Personal Protection

Control parameters

Component	OSHA Hazardous Components (29 CFR1910.1200)	
	Exposure Limits	
	OSHA PEL	ACGIH TLV
Stearic Wax (mixture)	None	None
Olefin Wax	None	None
Solid Saturated Hydrocarbon	None	None
Hydrated Amorphous Silica	80 mg/m ³ (total dust) %sio ₂	10 mg/m ³
Proprietary surface agent	None	None
Proprietary surface agent	None	None


Workplace Exposure Limits

Chemical specific exposure limits have not been established for the components of this material. However, due to

SAFETY DATA SHEET
APEX Superlube Mid Dens SM
Lubricant

the material's physical characteristics, it may become a nuisance dust hazard. The workplace exposure limits for nuisance dusts are:

- 15 mg/m³ OSHA PEL (total particulates not otherwise classified)
- 5 mg/m³ OSHA PEL (respirable fraction particulates not otherwise classified)
- 10 mg/m³ ACGIH TLV (total particulates not otherwise classified)

Exposure Controls	
Engineering Measures/Controls	Local exhaust ventilation should be applied whenever there is an incidence of point source emissions or dispersion of regulated contaminants in the work area. Ventilation control of the contaminant as close to its point of generation is both the most economical and safest method to minimize personnel exposure to airborne contaminants.
Personal Protective Equipment	
Pictograms	
Respiratory	Where exposure may exceed OSHA or ACGIH permissible air concentrations, a dust respirator is required.
Hands	Gloves are appropriate for exposure that exceeds permissible limits.
Eye/Face	Use chemical goggles where eye contact may occur.

General Industrial Hygiene	Handle in accordance with good industrial hygiene and safety practice. Wash thoroughly with soap and water after handling and before eating, drinking, or using tobacco. Safety shower and eye wash should be available close to work areas.
Environmental Exposure Controls	Follow best practices for the site management and disposal of waste. Avoid release to the environment.

Key to abbreviations

ACGIH = American Conference of Governmental Industrial Hygiene
 NIOSH = National Institute of Occupational Safety and Health
 = Occupational Safety and Health Administration
 MSHA = Mine Safety and Health Administration

TWA = Time-Weighted Averages are based on 8h/day, 40h/week exposures
 STEL = Short Term Exposure Limits are based on 15-minute exposures OSHA
 STEV = Short Term Exposure Value

Section 9 - Physical and Chemical Properties

Material Description			
Appearance/Description	Off-white powder	Odor	Odorless
Color	Off-white	Odor Threshold	N/A
Particulate Size	Not relevant	Particulate Type	Not relevant
Physical Form	Powder	Taste	Data lacking

SAFETY DATA SHEET
APEX Superlube Mid Dens SM
Lubricant

General Properties			
Auto-ignition	N/A	Melting Point	100° C Initiation
Boiling Point	N/A	Octanol/Water Partition coefficient	Data lacking
Decomposition Temperature	150° C Initiation	pH	Data lacking
Evaporation Rate	N/A	Specific Gravity/Relative Density	1.081
Flammability (solid, gas)	N/A	Vapor Density	N/A
Flash Point	N/A	Vapor Pressure	N/A
Heat of Decomposition		Viscosity	N/A
LEL	N/A	Water Solubility	Insoluble

Section 10 – Stability and Reactivity

Reactivity	Stable at room temperature.
Chemical Stability	Stable under normal temperatures and pressures.
Possibility of hazardous reactions	Hazardous polymerization will not occur.
Possibility of hazardous reactions	Oxidizers
Incompatible materials	N/A
Hazardous decomposition products	Carbon monoxide and carbon dioxide. Other products may be generated. Use in well-ventilated areas and avoid breathing or contacting solid and gaseous products of decomposition.

Section 11 - Toxicological Information

Information on toxicological effects	
Reported Human Effects:	Products/Similar Product – No human data are available for this product.
Reported Animal Effects:	Products/Similar Product – No animal data are available for this product.
Route(s) of entry/exposure	Inhalation, Skin, Eye, Ingestion
Inhalation:	
Acute (Immediate)	May cause irritation as a nuisance dust
Chronic (Delayed)	No data available
Skin:	
Acute (Immediate)	Causes skin irritation

SAFETY DATA SHEET
APEX Superlube Mid Dens SM
Lubricant

Chronic (Delayed)	Repeated and prolonged exposure may cause dermatitis
Eye:	
Acute (Immediate)	May cause mild eye irritation
Chronic (Delayed)	No data available
Ingestion:	
Acute (Immediate)	May cause irritation
Chronic (Delayed)	No data available

Section 12 - Ecological Information

Toxicity	Material data lacking
Persistence and degradability	Material data lacking
Bio-accumulative potential	Material data lacking
Mobility in Soil	Material data lacking
Other adverse effects	Not available
Other Information	Not available

Section 13 - Disposal Considerations

Waste treatment methods	
Product waste	Material data lacking
Packaging waste	Material data lacking

Section 14 - Transport Information

Special precautions for user	<p>Transport information: UN Number : Not classified as hazardous. UN Proper shipping name : N/A Transport hazard class : Not classified as hazardous. Packing group : N/A Environmental hazards : Not considered marine pollutant. : Not considered environmentally hazardous. Special precautions : Keep sealed and secure. Do not expose to heat. DOT Classification : Non-Hazardous. INCO Terms : EXW for Regulatory Purposes and Responsibilities MICRO POWDERS, INC. Regulatory information: Please request our Regulatory Summary Sheet (RSS) for global regulatory information. REACH: The reporting process for each substance has been or will be completed in accordance with the appropriate tonnage bands and registration deadlines. T.S.C.A: This product or its components are listed on the TSCA Inventory. This product or its components do not contain any chemicals subject to any</p>
-------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SAFETY DATA SHEET
APEX Superlube Mid Dens SM
Lubricant

	<p>rules or orders under TSCA sections 4, 5, 6, 7, or 8(d). CALIFORNIA PROP65 INFORMATION: Not Regulated. WHMIS CLASSIFICATION (CANADA): Not subject to WHMIS regulations. SARA TITLE III: This product is subject to SARA Title III reporting? Section 311/312: Immediate/Acute Health (irritant): YES Section 302: Contains an extremely hazardous substance: NO Section 313: This product does not contain any toxic chemical listed under Sec.313 of the Emergency Planning and Community Right-To-Know Act of 1986. CLEAN WATER ACT - Priority Pollutants: Contains no known priority pollutants at concentrations greater than 0.1%.</p>
--	------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

EPA					
CAS Number	Chemical Name	Sec. 302 (EHS) TPQ (in pounds) ¹	EHS RQ (in pounds) ²	CERCLA Reportable Quantity (in pounds) ³	Subject to Sec. 313 Reporting ⁴
110-30-5	Stearic Wax (mixture)	not listed	not listed	not listed	not listed
9002-88-4	Olefin Wax	not listed	not listed	not listed	not listed
68153-22-0	Solid Saturated Hydrocarbon	not listed	not listed	not listed	not listed
31570-04-4	Proprietary surface agent	not listed	not listed	not listed	not listed
149-57-5	Proprietary surface agent	not listed	not listed	not listed	not listed
112926-00-8	Hydrated Amorphous Silica	not listed	not listed	not listed	not listed

¹ The presence of EHSs in quantities in excess of the Threshold Planning Quantity (TPQ) requires certain emergency planning activities to be conducted. (Appendix B to 40 CFR 355)

² Releases of reportable quantities (RQ) of EHSs are subject to state and local reporting under section 304 of SARA Title III (EPCRA). (40 CFR 302.4)

³ Releases of CERCLA hazardous substances, in quantities equal to or greater than their reportable quantity (RQ), are subject to reporting to the National Response Center under CERCLA. (Appendix A to 40 CFR 172.101)

⁴ Emissions, transfers, and waste management data for chemicals listed under section 313 must be reported annually as part of the community right-to-know provisions of SARA Title III (EPCRA) (40 CFR Part 372).

SAFETY DATA SHEET
APEX Superlube Mid Dens SM
Lubricant

Section 16 - Other Information

Last revision date	5/7/15
Preparation date	5/7/15

Disclaimer/statement of liability

The information contained herein is believed to be accurate but is not warranted to be so. Data and calculations are based on information furnished by the manufacturer of the product and manufacturers of the components of the product. Users are advised to confirm in advance of need that information is current, applicable and suited to the circumstance of use. Vendor assumes no responsibility for injury to vendee or third persons proximately caused by the material if reasonable safety procedures are not adhered to as stipulated in the data sheet. Furthermore, vendor assumes no responsibility for injury caused by abnormal use of this material even if reasonable safety procedures are followed. Any questions regarding this product should be directed to the manufacturer of the product as described in Section 1.
